



Wall-Mount Sink Installation

Tools Needed:

- Screwdriver
- Drill & Bits
- Level
- Plumbers Basin
- Wrench to secure
Faucet (Optional)
- Wrench
- Pencil
- Tape Measure
- Plumbers Putty

Be sure to re-inforce wall before installation.
We recommend a 2"x12" securely fastened to wall studs at the desired height for your installation.

Installation Instructions

**** Be sure water supply is turned off before beginning.**

1. Determine the height you want. Place basin against the wall. Use a level to make sure both sides are level. Mark location on wall for mounting holes on back of sink.
2. Position each metal mounting bolt against the underside rear of basin and against the wall. Mark the location of mounting holes on the wall.
3. Remove the basin from the wall. Wall should be reinforced before continuing.
4. Start to drill hole in 2"x12" re-inforced wall for mounting hardware. Screw large wood screws provided into wall.
5. Before replacing basin, it would be convenient at this point to mount the faucet according to the manufacturer's instructions.
6. Slide sink onto bolts and ensure that it is level. Slide plastic flange washers and metal washers onto bolts. Thread hex nuts on snugly.
7. Ensure that it is level, and secure sink to wall using bolts through holes in back of sink.

- Connect all supply tubes to the faucet. Connect trap and drain assembly as described by the
8. manufacturer.