



## THE DO'S & DON'TS OF PROPER TEAK SINK CARE

Our low odor natural finish is very resistant when cured. This doubles the timber's natural durability to resist, scratching, gouging and other mechanical damage. However even treated teak can be scratched or damaged by hard materials such as metal so proper cleaning and maintenance is strongly suggested. Here is a helpful list of do's and don'ts for sink cleaning and maintenance:

### **CLEANING:**

DO: Clean with a soft damp cloth and wipe dry immediately to eliminate water spots or soap build-up.

DO: Reseal your sink. Your sink has been sealed with a wood sealant. When water does not bead-up or sit on the finish, we recommend you reseal your sink.

DO: Install properly. For drain installation, it is extremely important that your sink is installed perfectly flush, level and no water remains in the sink after use. Add a thin layer of clear silicone in the drain area and allow it to dry overnight before installing. This will add one more layer of protection.

DON'T use any abrasive cleaning materials or cleaning pads.

### **SCRATCHES, DENTS AND OTHER SMALL DAMAGES:**

Scratches can be made to appear less visible by applying a wood sealant on a cloth and rubbing over the damaged area. Work the sealant into the affected part of wood and then carefully pat off excess sealant with a dry cloth. Finish with buffing.

Small holes and dents may be repaired by using a wood filler. Pick the closest matching color and apply to wood following manufacturer's instructions. Reseal sink with wood sealant on affected area once dried or cured.

Eliminate scratches completely by sanding carefully. Reseal after sanding.

For long term maintenance, please consider using our Multi Surface Maintenance Wax. Wax is available from Magnus Home Products by following the link below:

<https://www.magnushomeproducts.com/products/multi-surface-maintenance-wax>